


Simple care quidelines



Ensuring that the AQUAvalve floods and drains correctly

- Making sure your AQUAvalve floods and drains correctly is simply achieved and only takes a few seconds.
- Hold the AQUAvalve at eye level so that you can see the silicon fitted to the top float resting on the hole below it.
- The silicon must create a tight seal when touching the hole.
- If it looks like it is not sitting parallel on the hole below, simply lift the top float and apply pressure to one side of the silicon, drop the float and hold at eye level again. Repeat the procedure if necessary.

Care and maintenance

1 At the end of your growing season, clean the AQUAvalve using warm soapy water. Using an old tooth brush will help.

The AQUAvalve is easily disassembled. The top float will slide all the way across and the bottom float is unclipped from its pivoting position. The circular discs fitted to the top float can also be removed by using pliers to grip the raised point.

At this point is it advisable to remove the silicones to avoid them being lost.

It is also handy to have a paper clip or pipe cleaner to hand so that you can push it through the AQUAvalve nozzle, this will remove any lime scale build up that may have occurred during the growing season.

Blowing through the AQUAvalve nozzle will also help to remove any build up. Do not under any circumstances use a drill & drill bit to clear the AQUAvalve nozzle.

This will potentially damage the AQUAvalve beyond repair.

Your 24Pot system set-up guidelines





24Pot system contents

- 1x 105 aallon FlexiTank
- 1x 1/2"click-fit tank adaptor & filter
- 32ft of 1/2" pipe
- 2x ½" in-line tap
- 1x 1/2" tee connector
- 12x 1/2"-1/4" cross connector


24x 1Pot trays & lids

- 24x 1Pot trays & lid • 24x 3.9 gallon pot
- 24x AQUAvalve
- 39ft of 1/4" pipe
- 24x Root Control Disc

Plan views and options

Suggested layout

System requires minimum 105 gal FlexiTank (supplied)





AQUAvalve



 $\frac{1}{2}$ " click-fit tank adaptor & filter

___ ¼" pipe

½" pipe

½" tee connector


► ½" – ¼" cross connector

½" in-line tap

Advice

- Pot up your plants, water through, then allow your plants to establish in the pots for a period of 7 to 10 days before turning your system on. This will encourage a stronger and healthier root system.
- Always raise your reservoir/FlexiTank to a minimum of 6" above the highest AQUAvalve and re-fill the
 reservoir/FlexiTank when there is approximately a 1/3 of the solution left NEVER ALLOW THE RESERVOIR/
 FLEXITANK TO RUN EMPTY.
- For best results, we recommend mineral fertilisers. Do not use organic fertilisers, as they have a tendency to block small pipe work.
- Clean all substrate from the bottom and sides of the pots before placing in each tray.
 This will ensure your system is clean from the start.
- Always use free draining substrates, for example: soil/perlite, coco/perlite, soil/clay pebbles, coco/clay pebbles, rockwool/clay pebbles.

1Pot dimensions







1Pot setup instructions



Put root control disc in pot



Fill pot with medium and pot up plants.

Water through pot and allow to drain outside the tray



Remove collar

Push 1/4" pipe through collar and attach to AQUAyalve nozzle

Rescrew collar - **DON'T overturn...** when you
feel it grip **STOP**



Connect AQUAvalve so 'half moon' is on T section in the tray



Position tray so it is level



Cut 1/4" / 1/2" pipe to appropriate length



According to the size of your system connect your $\frac{1}{4}$ / $\frac{1}{2}$ pipe to relevant fitting or reservoir.



Place pot in the tray, make sure it is **CLEAN!** Place lid over valve

onto tray

Using your front instruction sheet, repeat the module set up instructions for the number of trays.

Allow your plants to establish for 7-10 days before turning system on